

B.E.G.**LUXOMAT®**

Indoor 180-R-11-48V-3A covering included

Prod.No. 92621 EAN: 4007529926213

- Voltage: 11 - 48 V AC / DC
- Dimensions: covering included 87 x 87 x 61 mm
- Power consumption: approx. 1 W

Order data

| Designation | Colour | Art.No |
|--|------------|--------|
| Indoor 180-R-11-48V-3A covering included | pure white | 92621 |

Accessories

| Designation | Colour | Art.No |
|-------------------------------------|---------------|--------|
| Frame IP20 Indoor 180 | pure white | 92630 |
| Frame IP20 Indoor 180 | traffic white | 92631 |
| Frame IP20 Indoor 180 | anthracite | 92634 |
| Frame IP54 Indoor 180 | pure white | 92139 |
| Frame IP20 Indoor 180 | oyster white | 92632 |
| Frame IP20 Indoor 180 | silver | 92633 |
| Surface mounting socket Indoor 180 | pure white | 92141 |
| Central plate Indoor 180 45x45 | traffic white | 38947 |
| Central plate Indoor 180 45x45 | oyster white | 39076 |
| Central plate Indoor 180 55 x 55 mm | pure white | 39222 |
| Central plate Indoor 180 55 x 55 mm | signal white | 39241 |
| Central plate Indoor 180 55x55 | traffic white | 39242 |

| | | |
|---|------------|-------|
| Central plate Indoor 180 S1 56x56 | pure white | 35126 |
| Central plate Indoor 180 56x56 modular2 | pure white | 35127 |
| Blinds Indoor 180 transparent | | 92294 |
| Blind Indoor 180 | | 33233 |

Technical data

| | |
|--|--|
| Voltage: | 11 - 48 V AC / DC |
| Dimensions: | covering included 87 x 87 x 61 mm |
| Power consumption: | approx. 1 W |
| Detection area: | horizontal 180° (Wall mounting) |
| Range: | max. 10 m across max. 3 m towards |
| Monitored area (tangential movement): | 150 m ² / 1.1 m mounting height |
| Mounting height min./max./recommended: | 1 m / 2.2 m / 1.1 m |
| Degree / class of protection: | IP20 / Class II |
| Impact strength: | IK05 |
| Ambient temperature: | -25 °C to +50 °C |
| Housing: | polycarbonate, UV-resistant |
| Material color: | pure white mat, similar to RAL9010 |

Channel 1 (lighting control, potential-free (dry))

| | |
|----------------------|--------------------------------|
| Switching power: | 3 A; cos ϕ = 1 |
| Type of contact (k): | μ -contact, dry NO contact |
| Follow-up time: | 15 sec - 16 min, Pulse |
| Switch-on threshold: | 5 - 2000 Lux |

Product information

Wall motion detector with acoustic sensor, operating voltage 11-48 V

One potential-free switching channel

Acoustic sensor independently adjustable

Noise automatically extends follow-up time


Manual switching via push-button possible

Available with covering (centre plate dimensions 60 x 60 mm) or without covering for use with covering (centre plate dimensions 50 x 50 mm) in 5 different colours

In combination with centre plates usable with current frame systems of various manufacturers

B.E.G. frames and centre plates for combination with other frame systems available

Application examples: monitoring of public lavatories, corridors, archive rooms, conference rooms



Accessories



Frame IP20 Indoor 180
Art.No: 92630

Dimensions: 86 x 86 mm
Degree / class of protection: IP20
Housing: polycarbonate, UV-resistant



Frame IP20 Indoor 180
Art.No: 92631

Dimensions: 86 x 86 mm
Degree / class of protection: IP20
Housing: polycarbonate, UV-resistant



Frame IP20 Indoor 180
Art.No: 92634

Dimensions: 86 x 86 mm
Degree / class of protection: IP20
Housing: polycarbonate, UV-resistant



Frame IP54 Indoor 180
Art.No: 92139

Dimensions: 87 x 87 mm
Degree / class of protection: IP54
Housing: polycarbonate, UV-resistant



Frame IP20 Indoor 180
Art.No: 92632

Dimensions: 86 x 86 mm
Degree / class of protection: IP20
Housing: polycarbonate, UV-resistant



Frame IP20 Indoor 180
Art.No: 92633

Dimensions: 86 x 86 mm
Degree / class of protection: IP20
Housing: polycarbonate, UV-resistant



Surface mounting socket Indoor 180
Art.No: 92141

Dimensions: 88 x 88 x 42 mm
Degree / class of protection: IP54
Impact strength: IK05



Central plate Indoor 180 45x45
Art.No: 38947

Dimensions: 45 x 45 mm
Material color: traffic white mat,
similar to RAL9016



Central plate Indoor 180 45x45
Art.No: 39076

Dimensions: 45 x 45 mm
Housing: polycarbonate, UV-resistant
Material color: oyster white mat,
similar to RAL1013



Central plate Indoor 180 55 x 55 mm

Art.No: 39222

Dimensions: 55 x 55 mm
Housing: polycarbonate, UV-resistant
Material color: pure white glossy, similar to RAL9010



Central plate Indoor 180 55 x 55 mm

Art.No: 39241

Dimensions: 55 x 55 mm
Housing: polycarbonate, UV-resistant
Material color: signal white glossy, similar to RAL9003



Central plate Indoor 180 55x55

Art.No: 39242

Dimensions: 55 x 55 mm
Housing: polycarbonate, UV-resistant
Material color: traffic white glossy, similar to RAL9016



Central plate Indoor 180 S1 56x56

Art.No: 35126

Dimensions: 56 x 56 mm
Housing: polycarbonate, UV-resistant
Material color: pure white glossy, similar to RAL9010



Central plate Indoor 180 56x56 modular2

Art.No: 35127

Dimensions: 56 x 56 mm
Housing: polycarbonate, UV-resistant
Material color: pure white glossy, similar to RAL9010



Blinds Indoor 180 transparent

Art.No: 92294

Housing: polycarbonate, UV-resistant



Blind Indoor 180

Art.No: 33233

Housing: polycarbonate, UV-resistant
Material color: white