

**B.E.G.****LUXOMAT®**

## Indoor 180-R-11-48V-3A covering not included Set 92666-92633

- Voltage: 11 - 48 V AC / DC
- Dimensions: covering not included 70 x 70 x 61 mm
- Power consumption: approx. 1 W

### Areas of application

- entrance halls
- corridors/hallways
- staircases
- toilets
- equipment rooms

### Order data

| Designation                                  | Colour | Art.No |
|--|--------|--------|
| Indoor 180-R-11-48V-3A covering not included | -      | 92666  |
| Frame IP20 Indoor 180                        | silver | 92633  |

## Technical data

|  |   |
|--|---|
| Voltage:                               | 11 - 48 V AC / DC                             |
| Dimensions:                            | covering not included 70 x 70 x 61 mm         |
| Power consumption:                     | approx. 1 W                                   |
| Detection area:                        | horizontal 180° (Wall mounting)               |
| Range:                                 | max. 10 m across<br>max. 3 m towards          |
| Monitored area (tangential movement):  | 150 m <sup>2</sup> / 1.1 m mounting height    |
| Mounting height min./max./recommended: | 1 m / 2.2 m / 1.1 m                           |
| Degree / class of protection:          | IP20 / Class II                               |
| Impact strength:                       | IK05  |
| Ambient temperature:                   | -25 °C to +50 °C                              |
| Housing:                               | polycarbonate, UV-resistant                   |
| Material color:                        | <b>silver mat, similar to RAL9006 (92633)</b> |

### Channel 1 (lighting control, potential-free (dry))

|                      |                                |
|----------------------|--------------------------------|
| Switching power:     | 3 A; $\cos \varphi = 1$        |
| Type of contact (k): | $\mu$ -contact, dry NO contact |
| Follow-up time:      | 15 sec - 16 min, Pulse         |
| Switch-on threshold: | 5 - 2000 Lux                   |

## Product information

Set : Indoor 180-R-11-48V-3A covering not included + Frame IP20 Indoor 180 silver mat, similar to RAL9006

Wall motion detector with acoustic sensor, operating voltage 11-48 V

One potential-free switching channel

Acoustic sensor independently adjustable

Noise automatically extends follow-up time

Manual switching via push-button possible

Available with covering (centre plate dimensions 60 x 60 mm) or without covering for use with covering (centre plate dimensions 50 x 50 mm) in 5 different colours

In combination with centre plates usable with current frame systems of various manufacturers

B.E.G. frames and centre plates for combination with other frame systems available



## Set items

To receive the bundle according to the technical specification, please order the items listed.



**Indoor 180-R-11-48V-3A covering not included**  
Art.No: 92666

Voltage: 11 - 48 V AC / DC  
Dimensions: covering not included 70 x 70 x 61 mm  
Power consumption: approx. 1 W



**Frame IP20 Indoor 180**  
Art.No: 92633

Dimensions: 86 x 86 mm  
Degree / class of protection: IP20  
Housing: polycarbonate, UV-resistant