

**B.E.G.**

**LUXOMAT®**



## Indoor 180-S covering not included Set 92660-92139

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: **covering not included 70 x 70 x 61 mm + 87 x 87 mm (92139)**
- Power consumption: approx. 0.2 W

### Order data

| Designation                        | Colour     | Art.No |
|------------------------------------|------------|--------|
| Indoor 180-S covering not included | -          | 92660  |
| Frame IP54 Indoor 180              | pure white | 92139  |

## Technical data

|  |  |
|--|--|
| Voltage:                               | 110 – 240 V AC<br>50 / 60 Hz   |
| Dimensions:                            | <b>covering not included 70 x 70 x 61 mm + 87 x 87 mm (92139)</b>                |
| Power consumption:                     | approx. 0.2 W  |
| Detection area:                        | horizontal 180°<br>(Wall mounting)<br>max. 10 m<br>across<br>max. 3 m<br>towards |
| Range:                                 | 150 m <sup>2</sup> / 1.1 m<br>mounting<br>height                                 |
| Monitored area (tangential movement):  | 1 m / 2.2 m /<br>1.1 m   |
| Mounting height min./max./recommended: | <b>IP20 / Class II + IP54 (92139)</b>  |
| Degree / class of protection:          | IK05   |
| Impact strength:                       | -25 °C to +50 °C   |
| Ambient temperature:                   | polycarbonate,<br>UV-resistant   |
| Housing:                               | <b>pure white mat, similar to RAL9010 (92139)</b>                                |
| Material color:                        | 2 or 9 sec   |
| Pulse interval:                        |  |

## Product information

Set : Indoor 180-S covering not included + Frame  
IP54 Indoor 180 pure white mat, similar to RAL9010

Slave device

For extending the detection area of a Master device

Compatible with 230 V devices. Concerning exceptions please see the respective master device.

Available with covering (centre plate dimensions 60 x 60 mm) or without covering for use with covering (centre plate dimensions 50 x 50 mm) in 5 different colours

In combination with centre plates usable with current frame systems of various manufacturers

B.E.G. frames and centre plates for combination with other frame systems available



## Set items

To receive the bundle according to the technical specification, please order the items listed.



### Indoor 180-S covering not included

Art.No: 92660

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: covering not included 70 x 70 x 61 mm

Power consumption: approx. 0.2 W



### Frame IP54 Indoor 180

Art.No: 92139

Dimensions: 87 x 87 mm

Degree / class of protection: IP54

Housing: polycarbonate, UV-resistant