



## L8-LEDN

Prod.No. 94456 EAN: 4007529944569

- Voltage: 230 V AC  $\pm 10\%$  50 / 60 Hz
- Dimensions:  $\varnothing$  300 x 110 mm
- Luminous flux / intensity: LED circuit board securely mounted  
Colour temperature: 4000 K neutral white  
Luminous flux of LED: 1400 lm  
Luminous flux of light 1000 lm  
Peak: 312 cd

### Order data

Designation	Colour	Art.No
L8-LEDN	white	94456

## Technical data

Voltage:	230 V AC $\pm$ 10% 50 / 60 Hz
Dimensions:	Ø 300 x 110 mm LED circuit board securely mounted Colour temperature: 4000 K neutral white Luminous flux of LED: 1400 lm Luminous flux of light 1000 lm Peak: 312 cd
Luminous flux / intensity:	
Efficiency:	83 lm/W
Photobiological safety:	RG 0
Colour reproduction:	CRI 81.3 / TM30: 80.4
Rated life time:	50000 h (L80/B10)
Power consumption:	12 W / PF 0.94
Degree / class of protection:	IP40 / Class I
Impact strength:	IK02
Ambient temperature:	-20 °C to +40 °C
Housing:	Coated sheet steel case with LED circuit board, plastic cover Lens: PMMA diffuser, white
Material color:	white

## Product information


Round LED light for wall or ceiling mounting

Energy efficient light with long service life > 50,000 hours

Broad light distribution using diffused light covers

### Application examples:

corridors, halls, staircases, storage rooms, cellars, toilets



h (m)	Ø (m)	E (lx)
1.0	3.4	312
2.0	6.9	78
3.0	10.3	35
4.0	13.7	20
5.0	17.1	12

