

**B.E.G.**

**LUXOMAT®**



## PD2-S-SM Set 92152-92161

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: Ø 98 x 50 mm
- Power consumption: approx. 0.2 W

### Order data

Designation	Colour	Art.No
PD2-S-SM	white	92152
SM socket IP54 for PD2- / PD4-SM	white	92161

## Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	Ø 98 x 50 mm
Power consumption:	approx. 0.2 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated
Range:	
Monitored area (tangential movement):	78 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	IP20 / Class II
Impact strength:	IK05
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white mat, similar to RAL9010
Pulse interval:	2 or 9 sec

## Product information


Set : PD2-S-SM + SM socket IP54 for PD2- / PD4-SM  
white, similar to RAL9010

Slave device detector with circular detection area

For extending the detection area of a Master device

Trigger pulse to master device upon detected movement  
independent of the ambient light level

Compatible with 230 V devices. Concerning exceptions please  
see the respective master device.



## Set items

To receive the bundle according to the technical specification, please order the items listed.



### **PD2-S-SM**

Art.No: 92152

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 98 x 50 mm

Power consumption: approx. 0.2 W



### **SM socket IP54 for PD2- / PD4-SM**

Art.No: 92161

Dimensions: Ø 100 x 15 mm

Degree / class of protection: IP54

Housing: polycarbonate, UV-resistant