

B.E.G.**LUXOMAT[®]net**

PS-DALI-LINK-FC



Prod.No. 92846 EAN: 4007529928460

- Voltage: 110 - 277 V AC 50 / 60 Hz
- Dimensions: 240 x 26 x 26 mm
- Output voltage: 16 V DC (DALI, typical)

Order data

Designation	Colour	Art.No
PS-DALI-LINK-FC	white	92846

Technical data

Voltage:	110 – 277 V AC 50 / 60 Hz
Dimensions:	240 x 26 x 26 mm
Output voltage:	16 V DC (DALI, typical)
Power consumption:	3.3 W
Degree / class of protection:	IP20 / Class II
Ambient temperature:	-5 °C to +45 °C
Housing:	Polycarbonate + ABS mixture
Material color:	white
Connections and wires:	0.25 – 2.5 mm ² for solid conductors
Nominal current:	100 mA
Nominal current (max.):	120 mA

Product information

DALI power supply for the B.E.G. DALI-LINK multi room solution for installation in suspended ceilings.

Parameterisation of the DALI-LINK solution via Bluetooth with a smartphone and the B.E.G. DALI-LINK App.

For example, 25 DALI luminaires and 6 DALI-LINK control devices (multi-sensors or push-button interfaces) can be connected to the power supply.

It is possible to operate a maximum of one additional DALI-LINK power supply in parallel, doubling the number of DALI devices in the DALI-LINK system (50 DALI luminaires / 12 DALI-LINK control units).

Integrated temperature monitoring and short-circuit detection

Integrated LED for visualisation of operating information

DALI-2 certified product

This article is a component of a lighting control system from B.E.G., which supports the use of DALI control gear (luminaires, relays) from other manufacturers

The product can be used across manufacturers in accordance with the given DALI-2 product properties

Additional system components (hardware) are available from B.E.G.

Additional free software is available from B.E.G.

Suitable for: 93484, 93485, 93840, 93845, ...



